

DOCKET NO. 2002.04.003.WS0  
U.S. SERIAL NO. 10/080,889  
PATENT

**IN THE CLAIMS**

The current claims follow. For claims not marked as amended in this response, any difference in the claims below and the previous state of the claims is unintentional and in the nature of a typographical error.

1. (Previously Presented) For use in a base transceiver station of a wireless communications system, an apparatus for supporting dual standards comprising:

a sectored antenna system for a coverage area; and

an omni antenna system for the coverage area, wherein the sectored antenna system is employed for wireless communications utilizing a first standard within the coverage area and the omni antenna system is employed for wireless communications utilizing a second standard within the coverage area.

2. (Original) The apparatus according to claim 1, wherein one of the first and second standards is compatible with the other of the first and second standards.

3. (Original) The apparatus according to claim 2, wherein, upon failure of wireless communications utilizing the other of the first and second standards within the coverage area, wireless communications utilizing the other of the first and second standards within the coverage

DOCKET NO. 2002.04.003.WSO  
U.S. SERIAL NO. 10/080,889  
PATENT

area is resumed with the antenna system employed for the compatible one of the first and second standards.

4. (Original) The apparatus according to claim 1, wherein the first standard is IS-2000 and the second standard is one of 1xEV-D0 and 1xEV-DV.

5. (Original) The apparatus according to claim 1, wherein the first standard is one of 1xEV-D0 and 1xEV-DV and the second standard is IS-2000.

6. (Previously Presented) For use in a base transceiver station of a wireless communications system, an apparatus for supporting dual standards comprising:

a first coverage area employing a sectored antenna system for wireless communications utilizing a first standard within the first coverage area and a sectored antenna system for wireless communications utilizing a second standard within the first coverage area; and

a second coverage area employing a sectored antenna system for wireless communications utilizing the first standard within the second coverage area and an omni antenna system for wireless communications utilizing the second standard within the second coverage area.

7. (Original) The apparatus according to claim 6, wherein one of the first and second standards is compatible with the other of the first and second standards.

DOCKET NO. 2002.04.003.WSO  
U.S. SERIAL NO. 10/080,889  
PATENT

8. (Original) The apparatus according to claim 7, wherein, upon failure of wireless communications utilizing the other of the first and second standards within one of the first and second coverage areas, wireless communications utilizing the other of the first and second standards within the one of the first and second coverage areas is resumed with the antenna system employed for the compatible one of the first and second standards.

9. (Original) The apparatus according to claim 6, wherein the first standard is IS-2000 and the second standard is one of 1xEV-D0 and 1xEV-DV.

10. (Original) The apparatus according to claim 6, wherein the first standard is one of 1xEV-D0 and 1xEV-DV and the second standard is IS-2000.

11. (Previously Presented) For use in a base transceiver station of a wireless communications system, an apparatus for supporting dual standards comprising:

a first antenna system for wireless communications utilizing a first standard within a coverage area; and

a second antenna system for wireless communications utilizing a second standard within the coverage area,

DOCKET NO. 2002.04.003.WS0  
U.S. SERIAL NO. 10/080,889  
PATENT

wherein one of the first and second standards is compatible with the other of the first and second standards and, upon failure of wireless communications utilizing the other of the first and second standards within the coverage area, wireless communications utilizing the other of the first and second standards within the coverage area is resumed with the antenna system employed for the compatible one of the first and second standards.

12. (Original) The apparatus according to claim 11, wherein the first antenna system is a sectored system and the second antenna system is an omni system.

13. (Original) The apparatus according to claim 11, wherein the first antenna system is an omni system and the second antenna system is a sectored system.

14. (Original) The apparatus according to claim 11, wherein the first standard is IS-2000 and the second standard is one of 1xEV-D0 and 1xEV-DV.

15. (Original) The apparatus according to claim 11, wherein the first standard is one of 1xEV-D0 and 1xEV-DV and the second standard is IS-2000.

DOCKET NO. 2002.04.003.WS0  
U.S. SERIAL NO. 10/080,889  
PATENT

16. (Previously Presented) For use in a base transceiver station of a wireless communications system, a method of supporting dual standards comprising:

employing a sectored antenna system for wireless communications utilizing a first standard within a coverage area; and

employing an omni antenna system for the coverage area, wherein the sectored antenna system is employed for wireless communications utilizing a second standard within the coverage area.

17. (Original) The method according to claim 16, wherein one of the first and second standards is compatible with the other of the first and second standards.

18. (Original) The method according to claim 17, further comprising:  
upon failure of wireless communications utilizing the other of the first and second standards within the coverage area, resuming wireless communications utilizing the other of the first and second standards within the coverage area with the antenna system employed for the compatible one of the first and second standards.

19. (Original) The method according to claim 16, wherein the first standard is IS-2000 and the second standard is one of 1xEV-DO and 1xEV-DV.

DOCKET NO. 2002.04.003.WS0  
U.S. SERIAL NO. 10/080,889  
PATENT

20. (Original) The method according to claim 16, wherein the first standard is one of 1xEV-D0 and 1xEV-DV and the second standard is IS-2000.

21. (Previously Presented) For use in a base transceiver station of a wireless communications system, a method of supporting dual standards comprising:

employing a sectored antenna system for wireless communications utilizing a first standard within a first coverage area and a sectored antenna system for wireless communications utilizing a second standard within the first coverage area; and

employing a sectored antenna system for wireless communications utilizing the first standard within a second coverage area and an omni antenna system for wireless communications utilizing the second standard within the second coverage area.

22. (Original) The method according to claim 21, wherein one of the first and second standards is compatible with the other of the first and second standards.

23. (Original) The apparatus according to claim 22, further comprising:

upon failure of wireless communications utilizing the other of the first and second standards within one of the first and second coverage areas, resuming wireless communications utilizing the other of the first and second standards within the one of the first and second coverage areas with the antenna system employed for the compatible one of the first and second standards.

DOCKET NO. 2002.04.003.WS0  
U.S. SERIAL NO. 10/080,889  
PATENT

24. (Original) The method according to claim 21, wherein the first standard is IS-2000 and the second standard is one of 1xEV-D0 and 1xEV-DV.

25. (Original) The method according to claim 21, wherein the first standard is one of 1xEV-D0 and 1xEV-DV and the second standard is IS-2000.

26. (Previously Presented) For use in a base transceiver station of a wireless communications system, a method of supporting dual standards comprising:

employing a first antenna system for wireless communications utilizing a first standard within a coverage area;

employing a second antenna system for wireless communications utilizing a second standard within the coverage area, wherein one of the first and second standards is compatible with the other of the first and second standards; and

upon failure of wireless communications utilizing the other of the first and second standards within the coverage area, resuming wireless communications utilizing the other of the first and second standards within the coverage area with the antenna system employed for the compatible one of the first and second standards.

DOCKET NO. 2002.04.003.WS0  
U.S. SERIAL NO. 10/080,889  
PATENT

27. (Original) The method according to claim 26, wherein the first antenna system is a sectored system and the second antenna system is an omni system.

28. (Original) The method according to claim 26, wherein the first antenna system is an omni system and the second antenna system is a sectored system.

29. (Original) The method according to claim 26, wherein the first standard is IS-2000 and the second standard is one of 1xEV-D0 and 1xEV-DV.

30. (Original) The method according to claim 26, wherein the first standard is one of 1xEV-D0 and 1xEV-DV and the second standard is IS-2000.



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☒ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**